



SERIES 393

## SENSORS FOR SEISMIC TESTING

- Piezoelectric ICP® accelerometers, cables, and signal conditioners
- High sensitivity output
- Extended low frequency measurement capability
- Resolution down to 1.0  $\mu\text{g}$  rms
- Hermetically sealed, stainless steel or titanium housings
- Durable, water resistant connectors

### TYPICAL APPLICATIONS

- Smart infrastructure - foundation, floor vibration, and security monitoring
- Earthquake detection / sway fatigue analysis
- Structural testing of bridges and foundations
- Process monitoring inside machinery that is susceptible to low level vibration



### LOW FREQUENCY, HIGH OUTPUT ICP® ACCELEROMETERS

Earth tremors, foot, truck and automobile, road and bridge traffic, trains or other seismic events impart low frequency vibration on foundations intended to support these daily activities. These vibratory loads accumulate as stress and may degrade the structure. Smart infrastructure includes active measurement with real-time data logging that informs operators on structural integrity; critical during unforeseen loading scenarios. Cities of the future will manage not only new structures but those with critical or historical value, reducing potential for catastrophic failure.

PCB® is supporting advancements in sensor technology to take low frequency measurements to micro-g levels with ICP® accelerometers. In doing so, structural integrity data can be obtained on a routine, real-time basis. Permanently installed, high-output accelerometers are being mounted to bridges, walkways, highways, buildings, and other large structures to capture important trending data. Information gathered will aid engineers in evaluating structural integrity and alert communities when safety thresholds are approaching. This type of preventive maintenance can warn engineers that structural repair is necessary before a major catastrophe occurs.

SPECIFICATIONS						
Model Number	393A03	393B04	393B32	393B12	393B05	393B31
<b>Performance</b>						
Sensitivity	1.0 V/g	1.0 V/g	5.0 V/g	10 V/g	10 V/g	10 V/g
Measurement Range	±5.0 g pk	±5.0 g pk	±1.0 g pk	±0.5 g pk	±0.5 g pk	±0.5 g pk
Frequency Range (±5%)	0.5 to 2,000 Hz	0.06 to 450 Hz	0.2 to 200 Hz	0.15 to 1,000 Hz	0.7 to 450 Hz	0.1 to 200 Hz
Resonant Frequency	≥10,000 Hz	≥2,500 Hz	≥700 Hz	≥10,000 Hz	≥2,500 Hz	≥700 Hz
Broadband Resolution	0.00001 g rms	0.000003 g rms	0.000002 g rms	0.000008 g rms	0.000004 g rms	0.000001 g rms
Non-Linearity	≤1 %	≤1 %	≤1 %	≤1 %	≤1 %	≤1 %
Transverse Sensitivity	≤7 %	≤5 %	≤5 %	≤7 %	≤5 %	≤5 %
Overload Limit (Shock)	±5000 g pk	±300 g pk	±40 g pk	±5000 g pk	±300 g pk	±40 g pk
Base Strain Sensitivity	≤0.0005 g/με	≤0.0005 g/με	≤0.0005 g/με	≤0.0005 g/με	≤0.0005 g/με	≤0.0005 g/με
Temperature Range	-65 to +250 °F	-15 to +176 °F	-15 to +150 °F	-50 to +180 °F	-15 to +176 °F	-15 to +150 °F
<b>Electrical</b>						
Excitation Voltage	18 to 30 VDC	18 to 30 VDC	24 to 28 VDC	18 to 30 VDC	18 to 30 VDC	24 to 28 VDC
Constant Current Excitation	2 to 20 mA	2 to 10 mA	2 to 10 mA	2 to 20 mA	2 to 10 mA	2 to 10 mA
Output Impedance	<250 Ohm	<500 Ohm	≤500 Ohm	<1500 Ohm	<500 Ohm	≤500 Ohm
Output Bias Voltage	8 to 12 VDC	7 to 12 VDC	8 to 14 VDC	8 to 12 VDC	7 to 12 VDC	8 to 14 VDC
Discharge Time Constant	1 to 3 sec	5 to 15 sec	≥2 sec	≥3.5 sec	0.5 to 2.0 sec	≥5 sec
Settling Time	<15 sec	<100 sec	≤10 sec	<60 sec	<100 sec	60 sec
Spectral Noise (1 Hz) (Typical)	2 μg/√Hz	0.30 μg/√Hz	0.12 μg/√Hz	1.30 μg/√Hz	0.50 μg/√Hz	0.06 μg/√Hz
Spectral Noise (10 Hz) (Typical)	0.5 μg/√Hz	0.10 μg/√Hz	0.02 μg/√Hz	0.32 μg/√Hz	0.10 μg/√Hz	0.01 μg/√Hz
TEDS 1.0 version available (TLD)	–	Yes	–	–	Yes	–
<b>Physical</b>						
Sensing Element	Ceramic					
Sensing Geometry	Shear	Flexural	Flexural	Shear	Flexural	Flexural
Housing Material	Stainless Steel	Titanium	Stainless Steel	Stainless Steel	Titanium	Stainless Steel
Size - Diameter / Hex	1.18 in	0.99 in	2.25 in	1.18 in	0.99 in	2.25 in
Size - Height	2.18 in	1.22 in	2.80 in	2.18 in	1.22 in	2.80 in
Weight	210 gm (7.4 oz)	50 gm (1.8 oz)	635 gm (22.4 oz)	210 gm (7.4 oz)	50 gm (1.8 oz)	635 gm (22.4 oz)
Electrical Connector	2-Pin MIL-C-5015	10-32 Coaxial Jack	2-Pin MIL-C-5015	2-Pin MIL-C-5015	10-32 Coaxial Jack	2-Pin MIL-C-5015
Mounting Thread	1/4-28 Female	10-32 Female	1/4-28 Female	1/4-28 Female	10-32 Female	1/4-28 Female

Coaxial Cable Material & Type	Electrical Connectors	Cable Model by Length					
		3 ft	5 ft	10 ft	20 ft	30 ft	50 ft
		(0.9 m)	(1.5 m)	(3.0 m)	(6.1 m)	(9.1 m)	(15.2 m)
002 - White FEP, General Purpose	10-32 Plug to BNC Plug	002C03	002C05	002C10	002C20	002C30	002C50
003 - Blue TFE, Low Noise	10-32 Plug to BNC Plug	003C03	003C05	003C10	003C20	003C30	003C50
012 - Black PVC, RG58/U	2-Pin MIL-C-5015 to BNC Plug	–	012E05	012E10	012E20	–	012E50
012 - Black PVC, RG58/U	BNC Plug to BNC Plug	012A03	012A05	012A10	012A20	012A30	012A50



CE



**Basic 4-Channel ICP® Signal Conditioner**  
Model 482C05



**3425 Walden Avenue, Depew, NY 14043-2495 USA**  
Toll-Free in the USA: **800 828 8840**  
Phone: **1 716 684 0001** | Email: **info@pcb.com**

PCB Piezotronics, Inc. is a designer and manufacturer of microphones, vibration, pressure, force, torque, load, and strain sensors, as well as the pioneer of ICP® technology used by design engineers and predictive maintenance professionals worldwide for test, measurement, monitoring, and control requirements in automotive, aerospace, industrial, R&D, military, educational, commercial, OEM applications, and more. With a worldwide customer support team, 24-hour SensorLineSM, and a global distribution network, PCB® is committed to Total Customer Satisfaction. Visit [www.pcb.com](http://www.pcb.com) for more information. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corporation. Additional information on MTS can be found at [www.mts.com](http://www.mts.com).

© 2019 PCB Piezotronics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLineSM is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States.

TM-VIB-SEISMIC-1020



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.