

LC8406 Tank Weighing Accessories (BTW)





Features

- · Ball type
- · High resolution
- · Easy replacement

Material


- · OP1 : STEEL
- · OP2 : STAINLESS STEEL

Manual

- \cdot Rise the upper plate by using the supporters at both sides and join it with the base piate
- \cdot Untie the upper bolt of the supporter and place the upper ball cup over the steel ball
- \cdot Check the level of the load cell

Model	Capacity	А	В	С	D	Е	F	G	Н	ı	J	К	L	М	N
LC8406-T002TW	100kgf~2tf	180	15	90	60	120	90	15	14	107	20	20	17.4	Ø45	Ø29
LC8406-T005TW	3~5tf	230	20	110	80	150	110	20	18	135	30	25	30	Ø60	Ø45

ULK Ball Cup Accessories (Ball)



Accessory Features

- · High durability
- · Appropriate for tank and hopper application
- · Designed with safety coefficient considerations

Manual


- · Load cell connection with the mounting plate
- \cdot Fix the mounting plate on the surface
- · Check the level of the mounting plate
- \cdot Place the loading plate over the load cell
- \cdot Check the value with a display systems


Option

- · Steel
- · Stainless steel

Capacity	А	В	С	D	Е	F	G	Н	I
500kgf, 1tf, 2tf, 3tf	136	90			23	210×130	185×105	23	12
5tf	145	99	130×130	105×105	23	210×130	185×105	23	12
10tf	166	106	130×130	105×105	30	160×160	125×125	30	14
20, 30tf	196	136	130×130	105×105	30	200×200	160×160	30	14

ULK Tank Weighing Accessories (BTW)





Features


- · High durability
- · Appropriate for tank and hopper application
- · Designed with safety coefficient considerations
- · Prevention of separation by the bolt


Manual

- · Load cell connection with the mounting plate
- · Fix the mounting plate on the surface
- · Check the level of the mounting plate
- \cdot Place the loading plate over the load cell
- · Check the value with a display systems

Capacity	А	В	C	D	Е	F	G	Н	I	Н
500kgf, 1tf, 2tf, 3tf	105	105	130	210×130	185×105	210×130	136	23	23	4-Ø12 Thru
5tf	105	105	130	210×130	185×105	210×130	145	23	23	4-Ø12 Thru
10tf	105	105	160	220×160	125×125	220×160	166	30	30	4-Ø14 Thru
20tf, 30tf	105	105	200	270×200	160×160	270×200	196	30	30	4-Ø14 Thru

ULK Load Button Accessories (LB)





Accessory Features

- · High durability
- · Appropriate for tank and hopper application
- · Designed with safety coefficient considerations

Manual

- · Load cell connection with the mounting plate
- · Fix the mounting plate on the surface
- · Check the level of the mounting plate
- · Place the loading plate over the load cell
- · Check the value with a display systems

Option

- · Protection to breakaway
- · Steel
- · Stainless steel

Capacity	A	В	C	D	E	F	G	Н
0.5tf, 1tf, 2tf, 3tf	105	130×130	105×105	23	23	210×130	185×105	12
5tf	107	130×130	105×105	23	23	210×130	185×105	12
10tf	140	160×160	125×125	30	30	160×160	125×125	14
20tf	175	200×200	150×150	30	30	200×200	160×160	14