

Standard Type MI 711 Series

MI 711 Series

MI-711A(Standard Type)



MI-711P(Printer Type)



MI-711B(Battery Type)



Feature

- Platform Scale, Truck Scale, Tank Scale Application
- RS-232C Serial Interface(Current Loop) 1 port Standard built in
- Power Supply : DC12V/2A
- Display Size : MI-711A 1.0 inch(25.4(H) X 14.4(W)mm)
MI-711P 0.6 inch(14.1(H) X 8.1(W)mm)
- More powerful for dust & water proof
- CE Certification
- Only MI-711P with Small Industrial Printer Installation
(Paper size : 57 X 40 mm dia)

Specification

Specification	
Input Sensitivity	0.45μV/ Digit
Load Cell Excitation	DC5V
Max. Signal Input Voltage	Max.32mV
Temperature Coefficient	[Zero] ±20PPM/°C [Span] ±20PPM/°C
Input Noise	±0.6μV P.P
Input Impedance	Over 10MΩ
A/D Conversion Method	Sigma-Delta
A/D Resolution(Internal)	260,000 Count(18bit)
A/D Sampling Rate	Max. 80times / Sec
Non-Linearity	0.01% FS
Display Resolution(External)	1/90,000

MI-700 Series Dimension and Panel Cutting Size

UNIT:mm

